

AMENDMENTS TO THE CLAIMS

What is claimed is:

1. (Previously Presented) An output driver in a semiconductor memory device including a plurality of blocks of memory cells, wherein a first of the blocks transmits data to a data input/output line through the output driver, the output driver comprising:

a first transistor connected to a reference voltage, the first transistor being responsive to the data from the first block;

a second transistor between the first transistor and the data input/output line; and

a controller including a multiplexer coupled to control the second transistor, the controller being operable in a first mode in which the second transistor is responsive to a read control signal and a column cycle signal for selecting the first block, wherein the data from the first block is transmitted to the data input/output line via the first and second transistors.

2. (Original) The output driver of claim 1, wherein the controller deactivates the second transistor when a second of the blocks is selected for data output.

3. (Previously Presented) The output driver of claim 1, wherein the controller activates the second transistor by sending a read control signal and when the second transistor responds to the read control signal, the data from the first block is transmitted to the data input/output line via the first and second transistors.

4. (Previously Presented) The output driver of claim 1, wherein the controller is further operable in a second mode in which the second transistor is responsive to a read control signal containing calibration information about characteristics of the data input/output line.

5. (Previously Presented) The output driver of claim 4, wherein the controller comprises the multiplexer that selectively transmits one of the column cycle signal and the read control signal to the gate of the second transistor in response to a clock enable signal.

6. (Original) The output driver of claim 4, wherein the characteristics of the data input/output line comprise an output current (I_{OL}) characteristic for adjusting a signal level of the data input/output line and a temperature characteristic (T_{MIN}/T_{MAX}) for adjusting a slew rate of the output driver according to change in temperature.

7. (Currently Amended) A memory module comprising:

a plurality of semiconductor memory devices, each semiconductor memory device including a plurality of blocks of memory cells and a plurality of output drivers corresponding to the blocks, the blocks transmitting data through output drivers;

channel bus lines shared by [[the]] data input/output lines, wherein:

in one semiconductor memory device, the data of a selected block is transmitted to one of the channel bus lines via a corresponding output driver, which is activated in response to a column cycle signal selecting the block, and via one of the data input/output [[line]] lines, while in the remaining semiconductor memory devices sharing one of the channel bus [[line]] lines, the output drivers are all deactivated, and wherein

each output driver comprises:

a first transistor connected to a reference voltage, the first transistor responsive to the memory cell data; and

a second transistor is connected to a controller including a multiplexer, the second transistor is configured to selectively connect the first transistor to the one of the data input/output [[line]] lines in response to the column cycle signal or a read control signal containing calibration information about characteristics of the data input/output line.

8. (Currently Amended) The memory module of claim 7, wherein the second transistors of output drivers in the blocks are simultaneously activated when the second transistors respond to the read control signal, and the memory cell data of the selected block is transmitted to the one of the data input/output ~~[[line]]~~ lines via the first and second transistors.

9. (Original) The memory module of claim 7, further comprising a multiplexer for selectively transmitting one of the column cycle signal and the read control signal to the gate of the second transistor in response to a clock enable signal.

10. (Currently Amended) The memory module of claim 7, wherein ~~[[the]]~~ characteristics of the one of the data input/output ~~[[line]]~~ lines are an output current (I_{OL}) characteristic of adjusting the signal level of the data input/output line and a temperature characteristic (T_{MIN}/T_{MAX}) of adjusting the slew rate of the output driver according to change in temperature.

11. (Currently Amended) A semiconductor memory device comprising:
a plurality of output drivers; and
a plurality of blocks of memory cells corresponding to ~~[[an]]~~ and respectively coupled to the plurality of output drivers, wherein each block transmits data to through the corresponding output driver, wherein

each output driver comprises:

a first transistor connected to a reference voltage, the first transistor being responsive to the data from the corresponding block;

a second transistor connected to the first transistor; and

a controller including a multiplexer connected to control the second transistor, the controller being operable in a first mode in which the second transistor is responsive to a read control signal and a column cycle signal for selecting the block corresponding to the output driver and operable in a second mode in which the second transistor is responsive to the read control signal, wherein the data from the corresponding block is transmitted to the data input/output line via the first and second transistors.

12. (Currently Amended) The semiconductor memory device of ~~claim 1~~ claim 11, wherein the controllers deactivate the second transistors of the output drivers in unselected blocks.

13. (Previously Presented) The semiconductor memory device of claim 11, wherein:

the controllers activate simultaneously the second transistors of output drivers during the second mode;

the controller signal separately activates the associated second transistor of the output driver during the first mode.

14. (Original) The semiconductor memory device of claim 11, each controller comprising a multiplexer that selectively transmits one of the column cycle signal and the read control signal to the gate of the second transistor in response to a clock enable signal.

15. (Currently Amended) The semiconductor memory device of claim 11, wherein [[the]] characteristics of the one of the data input/output [[line]] lines comprise an output current (I_{OL}) characteristic for adjusting a signal level of the data input/output line and a temperature characteristic (T_{MIN}/T_{MAX}) for adjusting a slew rate of the output driver according to change a temperature.